

MG 4000 SD-5 – Tin 12

4kVA Tin 12 Diesel Generator

When looking for robust, reliable, good quality 4kVA Tin 12 diesel generator, look no further than our MG 4000 SD-5 – Tin 12. Fusion models are designed to suit Tin 12 gas and water applications for butt + electro boxes – 110V CTE.

Features

4kVA (110V) AC Aux Power
Linz alternator
Kohler/ Lombardini diesel engine (Stage 5)
HVO (Hydrotreated Vegetable Oil) fuel approved
Complete with trolley kit + folding handles
Only 76kg
Recoil starting system

Benefits

Plenty of power to run small gas and water applications
Heavy duty and proven reliability
Recoil start, power, reliability and robust strength
Suitable to run off either diesel, HVO or a mixture of both fuels
For nice and easy manoeuvrability and storage
Lightweight design
Simple and easy start

Recoil
start

HVO
FUEL
APPROVED

Silenced



Stage 5
Engine



LOMBARDINI
KOHLER
2 Year Engine
Warranty (Limited)

Specification

Performance

Alternator	Linz	Noise Level	LWA=95 dBa@7m=70
Single Phase Power (110V)	4kVA/ 3.2kW	Insulation Class	H
Single Phase Power (230V)	N/A	Mechanical Protection - IP	23

Engine

Make	Kohler/ Lombardini	Cooling	Air
Type	15LD350 (Stage 5)	Fuel Consumption @ 75% Load (Litres/hour)	1
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Fuel Tank Capacity (Litres)	13
Number of Cylinders	1	Average Runtime @ 75% Load (Hours)	13
Power (HP)	6.5	CO ₂ Output Per Hour @ 75% Load	2.62kg
Engine Speed (RPM)	3000	Starting System	Recoil

Dimensions (Machine only)

Length: 765 mm	Width: 525 mm	Height: 590 mm
Dry Weight (No Fuel): 84 kg		Wet Weight (Fuel Full): 97 kg

Dimensions (Trolley kit with handles folded out)

Length: 1460 mm	Width: 750 mm	Height: 725 mm
Dry Weight (No Fuel): 89 kg		Wet Weight (Fuel Full): 102 kg

Socket Configuration

MG 4000 SD-5 – Tin 12	1ph (110V)	
	32A	16A
	1	2

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk



GROUP
The Preferred Supplier

Designed in the UK,
built in Italy

