

MG 5000 - Tin 12

5kVA Tin 12 Petrol Generator

When looking for robust, reliable, good quality 5kVA Tin 12 petrol generator, look no further than our MG 5000 - Tin 12. Fusion models are designed to suit Tin 12 gas and water applications for butt + electro boxes - 110V CTE.

Optional





Engine



GX Engine 3 Year

5kVA (110V) AC Aux Power

NSM alternator

Honda petrol engine (Stage 5)

Strong wrap-around frame

Only 54kg

Features Benefits

Plenty of power to run small gas and water applications

Heavy duty and proven reliability and extra smooth wave form

Featuring low oil level shutdown

Great protection in tough environments

Lightweight design



Specification

Performance

Alternator	NSM K100F
Single Phase Power (110V)	5kVA/4kW
Single Phase Power (230V)	N/A

Noise Level	LWA=96	dBa@7m=71
Insulation Class		Н
Mechanical Protection	on - IP	23

Engine	
Make	Honda
Туре	GX270 (Stage 5)
Fuel	Petrol
Number of Cylinders	1
Power (HP)	8.5
Engine Speed (RPM)	3000

Cooling	Air
Fuel Consumption @ 75% Load (Litres/hou	r) 1.9
Fuel Tank Capacity (Litres)	5.3
Average Runtime @ 75% Load (Hours)	2.7
CO2 Output Per Hour @ 75% Load	4.56kg
Starting System	Recoil

Dimensions (Machine only)

Length: 690 mm	Width: 480 mm	Height: 540 mm
Dry Weight (No Fuel): 54 kg		Wet Weight (Fuel Full): 59 kg
Dimensions (Tallactic)		

Dimensions (Trolley kit)

Length: 810 mm	Width: 630 mm	Height: 730 mm
Dry Weight (No Fuel): 59 kg		Wet Weight (Fuel Full): 64 kg

Cooket Confirmation	1ph (110V)	
Socket Configuration	32A	16A
MG 5000 – Tin 12	1	2

For more details call MHM TODAY

on **0808 168 9099**









Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change.