

MG 4000 SD-RT

4kVA Railtrack Approved Diesel Generator

When looking for robust, reliable, good quality 4kVA Railtrack Approved diesel generator, look no further than our MG 4000 SD-RT.

Silenced

Recoil start

Features

Railtrack approved
4kVA (110V) CTE (55V-0-55V)
Linz alternator
Kohler/ Lombardini diesel engine
Complete with trolley kit + folding handles
Only 76kg
Recoil starting system

Benefits

Trackside ready
Plenty of power to run a variety of tools on site
Heavy duty and proven reliability
Recoil start, power, reliability and robust strength
For nice and easy manoeuvrability and storage
Extremely light weight
Simple and easy start



Specification

Performance

Alternator	Linz	Three Phase Power (400V)	N/A
Single Phase Power (110V)	4kVA/ 3.2kW	Noise Level	LWA=95 dBa@7m=70
Single Phase Power (230V)	N/A	Insulation Class	H
		Mechanical Protection - IP	23

Engine

Make	Kohler/ Lombardini	Fuel Consumption @ 75% Load (Litres/hour)	1
Type	15LD350	Fuel Tank Capacity (Litres)	13
Fuel	Diesel	Average Runtime (Hours)	
Number of Cylinders	1	@ 100% Load	TBA
Power (HP)	6.5	@ 75% Load	13
Engine Speed (RPM)	3000	@ 50% Load	TBA
Cooling	Air	@ 25% Load	TBA
		Starting System	Recoil

Dimensions (Machine only)

Length: 765 mm	Width: 525 mm	Height: 590 mm
Dry Weight (No Fuel): 71 kg	Wet Weight (Fuel Full): 84 kg	

Dimensions (Trolley kit with handles folded out)

Length: 1460 mm	Width: 750 mm	Height: 725 mm
Dry Weight (No Fuel): 76 kg	Wet Weight (Fuel Full): 89 kg	

Socket Configuration

	3ph (400V)		1ph (230V)		1ph (110V)	
	32A	16A	32A	16A	32A	16A
MG 4000 SD-RT	-	-	-	-	1	2



Designed in the UK, built in Italy

All pictures are for illustration purposes only, actual machines supplied may differ in appearance and specification.

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhplant.com or visit us at www.mhplant.com