

MG 15000 SSK-MV

Ready to Rent 15kVA Diesel Generator

Multi Voltage
400V 230V 110V

When looking for a robust, reliable, good quality 15kVA rental-friendly generator, our MG 15000 SSK-MV has everything the market requires.

Optional extras: Road-tow Kit Trolley kit GPS Telemetry Tracker

HVO FUEL APPROVED

READY TO RENT SPECIFICATION

Water Cooled Extra Super Silent

Features

- 15kVA Multi-Voltage AC Aux Power
- Linz (AVR) alternator
- Kubota diesel engine (Stage 3)
- HVO (Hydrotreated Vegetable Oil) fuel approved
- Exclusive MHM engine protection shutdown system
- 12V battery isolator switch
- Emergency stop button
- Central lifting eye and fork pockets
- Fully bunded base (110%)
- Engine oil drain pump

Benefits

- Hugely versatile with a massive advantage in the rental market
- Heavy duty and proven reliability
- World class performance and watercooled
- Suitable to run off either diesel, HVO or a mixture of both fuels
- In the case of low fuel, low oil pressure and battery charge failure
- Reduces flat battery breakdowns
- A must on any UK site
- Flexible and safe lifting on site
- To retain all spilt fluids
- Reducing service time



Stage 3 Engine

2

Year Warranty

Kubota
2 Year Engine Warranty (Limited)

Specification

Performance

Alternator	Linz (AVR)	Three Phase Power (400V)	15kVA/ 12kW
Single Phase Power (110V)	12kVA/ 9.6kW	Noise Level	LWA=88 dBa@7m=63
Single Phase Power (230V)	15kVA/ 12kW	Insulation Class	H
		Mechanical Protection - IP	23

Engine

Make	Kubota	Fuel Consumption @ 75% Load (Litres/hour)	3.7
Type	D1105 (Stage 3)	Fuel Tank Capacity (Litres)	40
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
Number of Cylinders	3	@ 100% Load	7
Power (HP)	26	@ 75% Load	10
Engine Speed (RPM)	3000	@ 50% Load	17
Cooling	Water	@ 25% Load	38
		CO ₂ Per Hour @ 75% Load (kg)	9.69
		Starting System	Deepsea 3110 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 1440 mm	Width: 810 mm	Height: 890 mm
Dry Weight (No Fuel): 425 kg	Wet Weight (Fuel Full): 465 kg	

Dimensions (Trolley kit with handles folded out)

Length: 2002 mm	Width: 990 mm	Height: 1050 mm
Dry Weight (No Fuel): 435 kg	Wet Weight (Fuel Full): 475 kg	

Dimensions (With road-tow kit)

Length: 2650 mm	Width: 1300 mm	Height: 1340 mm
Dry Weight (No Fuel): 560 kg	Wet Weight (Fuel Full): 594 kg	

Socket Configuration	3ph (400V)		1ph (230V)		1ph (110V)	
	32A	16A	32A	16A	32A	16A
MG 15000 SSK-MV	1	-	2	2	3	1
Hard wire facility	3ph (400V)		1ph (230V)		1ph (110V)	
MG 15000 SSK-MV	✓		✓		✓	

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk

Designed in the UK, built in Italy

GROUP
The Preferred Supplier