

Multi Voltage

400V <mark>230V</mark> 110V

MGTP 25 SSY-MV Ready to Rent 25kVA Diesel Generator

When looking for a robust, reliable, good quality 25kVA rental-friendly generator, our MGTP 25 SSY-MV has everything the hire market requires.

Optional extras:

Road-tow On GPS Telemetry Kit Tracker

Features

25kVA Multi-Voltage AC Aux Power (400V / 230V / 110V)

Linz alternator

Yanmar diesel	engine (Stage 3A)
HVO (Hydrotre fuel approved	ated Vegetable Oil)
Exclusive MHN protection shu	9
3 way fuel valv	e
12V battery iso	lator switch
Emergency sto	p button
Variable RCD	

Central lifting eye and fork pockets

Benefits Hugely versatile with a massive advantage in the rental market Heavy duty and proven reliability World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure, high engine temp and battery charge failure

Easy connectivity to an external fuel tank Reduces flat battery breakdowns

A must on any UK site Flexible protection

Turn off the ELR to avoid nusiance tripping when powering electrical motors Flexible and safe lifting on site

Three Phase Power (400V) 25kVA/ 20kW

To retain all spilt fluids Reducing service time Stage **3A** Engine

APPROVED

YANMAR 3 Year Engine Warranty (Limited)

Specification

Performance

ELR bypass switch

(activated by key only)

Engine oil drain pump

Fully bunded base (110%)

T CHIOTHIANCE			micernuse	i owci (2010	110/ 20101		
Alternator Linz (AVR Controlled)		ed)	Noise Level		LWA=88 dBa	@7m=63		
Single Phase Power (110V) 25kVA/ 20kW		W	Insulation Cl	ass		Н		
Single Phase Power (230V) 25kVA/ 20kW		W	Mechanical I	Protectio	on – IP	23		
Engine Fuel Consumption @ 75						Load (Litres/hc	our) 5	
	Make	Yanmar	Fue	el Tank Capacity	(Litres)		120	
Type TBA (Stage 3A)			Ave	Average Runtime (Hours)				
	Fuel Diesel / HVO (HVO = BS EN	15940:2016 Only)	@	100% Load	19	@ 75% Load	24	
	Number of Cylinders	4	@!	50% Load	39	@ 25% Load	75	
	Power (HP)	27	CO:	CO2 Per Hour @ 75% Load			13.1kg	
	Engine Speed (RPM)	1500	Cor	stral Danal	Dee	psea 3110 c/w	two wire	
	Cooling	Water	COI	Auto Start/ Stop facility			op facility	

Dimensions (Machine only)								
Length: 1850 mm	Wi	Width: 970 mm			Height: 1520 mm			
Dry Weight (No Fuel): 710 kg	Wet Weight (Fuel Full): 830 kg							
Dimensions (With road-tow kit)								
Length: 3310 mm	Width: 1625 mm Height: 1950 r				950 mm			
Dry Weight (No Fuel): 940 kg	g Wet Weight (Fuel Full): 1060 kg							
Socket	3ph (3ph (400V)		1ph (230V)		110V)		
Configuration	63A	32A	32A	16A	32A	16A		

Configuration	63A	32A	32A	16A	32A	16A
MGTP 25 SSY-MV	-	1	2	2	3	1
Hard wire facility	3ph (400V)		1ph (230V)		1ph (110V)	
MGTP 25 SSY-MV	 ✓ 		 ✓ 		V	

Designed in the UK.

built in Italy

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk



(in) (0)